

Linear Continuous

PRODUCT SPECIFICATION | FOURTH GENERATION

• PRODUCT STANDARD | + PRODUCT UPGRADE

LW-EB-LC-

PARAMETER	CODE	DESCRIPTION	CONDITIONALS	NOTES
01. SERIES	LW-EB	Linear Embedded		
02. MODEL	LC	Continuous		
03. LENGTH [L]		Total Length in Feet Min. 2' Increments of 1'	2'-4' available in R driver only	Final length confirmed in shop drawings
04. LIGHT DISTRIBUTION	DN UP DU +	Direct Indirect Direct + Indirect		
05. DRIVER	I R	Integrated Remote	I driver available for 5'+ only R driver coaxial cable standard subject to change based on power requirements and specified length	Confirmed in shop drawings
06. CIRCUIT	1C 2C +	1 Circuit 2 Circuit	For DU light distribution only	
07. DIMMING	010 • 020 DAL +	0-10V TRIAC/ELV DALI	For R driver only	Reduced warranty, see System Summary
08. LUMEN OUTPUT DIRECT	LO ST • HI +	650 lm/ft 6.2 W/ft 115.4 lm/W 1000 lm/ft 9.5 W/ft 110.2 lm/W 1514 lm/ft 14.4 W/ft 104.9 lm/W	Parameter 08 for DN or DU light distribution only	3500K, 90 CRI shown +/- 5% based on optics and CCT See parameters 8/9 for more information
09. LUMEN OUTPUT INDIRECT	LO ST • HI +	726.2 lm/ft 6.2 W/ft 128.9 lm/W 1117.2 lm/ft 9.5 W/ft 123.1 lm/W 1691.5 lm/ft 14.4 W/ft 117.2 lm/W	Parameter 09 for UP or DU light distribution only	3500K, 90 CRI shown +/- 5% based on optics and CCT See parameters 8/9 for more information
10. OPTICS DIRECT	LB • OV + W2 + W3 + AS +	Lambertian Oval ~40° + 100° Wide ~70° + 100° Extra Wide ~110° + 100° Asymmetric	Parameter 10 for DN or DU light distribution only	
11. OPTICS INDIRECT	LB BW • BX AS	Lambertian Batwing Wide ~145° + 100° Batwing Extra Wide ~165° + 130° Asymmetric	Parameter 09 for UP or DU light distribution only	
12. COLOUR TEMP	27K 30K 35K 40K	2700K Warm White 90+ CRI 3000K Soft White 90+ CRI 3500K Natural White 90+ CRI 4000K Cool White 90+ CRI		
13. WOOD	WAL OAK CHR MPL ASH EGW	Walnut White Oak Cherry Hard Maple White Ash Engineered Wood		End caps match
14. WOOD FINISH: CLEAR	CFST • CFDO + CFEC	Clear Finish Satin Danish Oil ECO Coat Zero VOC		End caps match Clear finish on EGW will have live edge visible
WOOD FINISH: PAINTED	PFBK PFWH PFXX +	Painted Finish Satin Black Painted Finish Satin White Painted Finish Custom	For ASH and EGW wood types only	End caps match

Linear Continuous

PRODUCT SPECIFICATION | FOURTH GENERATION

• PRODUCT STANDARD | + PRODUCT UPGRADE

LW-EB-LC-

01	02	03/04	05	06	07	08	09	10	11	12	13	14	15	16	17/18	19	20
PARAMETER					CODE	DESCRIPTION			CONDITIONALS				NOTES				
15. FENIX [OPTIONAL]					FXBK +	Bianco Kos							Applied to sides of fixture				
					FXVC +	Verde Comodoro											
					FXBF +	Blu Fes											
					FXGB +	Grigio Bromo											
					FXNI +	Nero Ingo											
					FXXX +	Custom											
16. CANOPY COLOUR					WH •	White											
					BK	Black											
					XX +	Custom											
17. CABLE COLOUR					W •	White			For I drivers only								
					B	Black			For I drivers only								
					C	Clear Jacket with Silver Core			For R drivers only								
18. CABLE LENGTH						In Feet							On-site adjustable				
						5' standard • 6' and above +											
19. MOUNTING					IN •	Integrated			For I drivers only								
					JB	Junction Box			For I drivers only								
					TB	T-Bar Support			For I + R drivers		For 15/16" t-bar width						
					PO	Power Over Cable			For R drivers only								
20. CANOPY HARDWARE					MI •	Minimal			Parameter 21 for JB mounting type only								
					MA	Match											

CUSTOM NOTES