

Linear Continuous

PRODUCT SPECIFICATION | THIRD GENERATION

• PRODUCT STANDARD | + PRODUCT UPGRADE

LW-EB-LC-

Series Model

03/04

05

06

07

08

09

10

11

12

13

14

15

16

17/18

19

20

PARAMETER	CODE	DESCRIPTION	CONDITIONALS	NOTES
01. SERIES	LW-EB	Linear Embedded		
02. MODEL	LC	Continuous		
03. LENGTH [L]		Total Length in Feet Min. 5' Increments of 1'		Final length confirmed in shop drawings
04. LIGHT DISTRIBUTION	DN UP DU +	Direct Indirect Direct + Indirect		
05. DRIVER	I R	Integrated Remote		
06. CIRCUIT	1C 2C +	1 Circuit 2 Circuit	For DU light distribution only	
07. DIMMING	010 • 020 DAL +	0-10V TRIAC/ELV DALI	For R drivers only	Reduced warranty, see System Summary
08. LUMEN OUTPUT DIRECT	LO ST • HI +	650 lm/ft 6.19 W/ft 105 lm/W 1000 lm/ft 9.5 W/ft 105 lm/W 1514 lm/ft 14.4 W/ft 105 lm/W		+/- 5% based on optics and CCT See parameters 8/9 for more information
09. LUMEN OUTPUT INDIRECT	LO ST • HI +	726.2 lm/ft 6.19 W/ft 117.3 lm/W 1117.2 lm/ft 9.5 W/ft 117.2 lm/W 1691.5 lm/ft 14.4 W/ft 117.2 lm/W	Parameter 09 for DU light distribution only	+/- 5% based on optics and CCT See parameters 8/9 for more information
10. OPTICS DIRECT	LB • OV + WW + XW + AS +	Lambertian Oval ~40° + 100° Wide ~70° + 100° Extra Wide ~110° + 100° Asymmetric		
11. OPTICS INDIRECT	LB BW • BX AS	Lambertian Batwing Wide ~145° + 100° Batwing Extra Wide ~165° + 130° Asymmetric	Parameter 11 for DU light distribution only	
12. COLOUR TEMP	27K 30K 35K 40K	2700K Warm White 90+ CRI 3000K Soft White 90+ CRI 3500K Natural White 90+ CRI 4000K Cool White 90+ CRI		
13. WOOD	WAL OAK CHR MPL ASH EGW	Walnut White Oak Cherry Hard Maple White Ash Engineered Wood		
14. WOOD FINISH: CLEAR	CFST • CFDO + CFEC	Clear Finish Satin Danish Oil ECO Coat Zero VOC		End caps are brushed aluminum Clear finish on EGW will have live edge visible
WOOD FINISH: PAINTED	PFBK PFWH PFX +	Painted Finish Satin Black Painted Finish Satin White Painted Finish Custom	For ASH and EGW wood types only	End caps match

Linear Continuous

PRODUCT SPECIFICATION | THIRD GENERATION

• PRODUCT STANDARD | + PRODUCT UPGRADE

LW-EB-LC-

Series Model

03/04

05

06

07

08

09

10

11

12

13

14

15

16

17/18

19

20

PARAMETER	CODE	DESCRIPTION	CONDITIONALS	NOTES
15. FENIX [OPTIONAL]	FXBK + FXVC + FXBF + FXGB + FXNI + FXXX +	Bianco Kos Verde Comodoro Blu Fes Grigio Bromo Nero Ingo Custom		
16. CANOPY COLOUR	WH • BK XX +	White Black Custom		
17. CABLE COLOUR	W • B C	White Black Clear Jacket with Silver Core	For I drivers only For I drivers only For R drivers only	
18. CABLE LENGTH		In Feet 5' standard • 6' and above +		On-site adjustable
19. MOUNTING	IN • JB TB PO	Integrated Junction Box T-Bar Support Power Over Cable	For I drivers only For I drivers only For I + R drivers For R drivers only	For 15/16" t-bar width
20. CANOPY HARDWARE	MI • MA	Minimal Match	Parameter 21 for JB mounting type only	

CUSTOM NOTES