

Post + Beam Table Light

METAL SHADE EDITION

SPECIFICATIONS

SERIES	COLLECTION	MODEL
LW-EB	PB	TB

LUMEN OUTPUT

LO: 650 lm/ft | 6.2 W/ft | 115.4 lm/W

ST: 1000 lm/ft | 9.5 W/ft | 110.2 lm/W

HI: 1514 lm/ft | 14.4 W/ft | 104.9 lm/W

POWER INPUT

110-277V AC | 50/60 Hz

WEIGHT

<1 kg per foot

OPTICS

Opal diffuser

HARDWARE

Concealed table anchors with tamper-proof fasteners

PRODUCT INFO

MANUFACTURED IN

Toronto, ON, Canada

WARRANTY

5 years

Reclamation program available

CERTIFICATIONS

Rated for dry or damp locations



DRIVER COMPATIBILITY ⓘ

Product specification and material selection will be confirmed at shop drawing stage.

LW-EB-PB-TB-MS



aaline's Post + Beam Collection is designed for focused, high-quality lighting for high-traffic, commercial, and institutional projects. Enhanced with anti-glare carved visors (UGR<16) and 90+ CRI LED chips, the Post + Beam Series holds the highest-performing light fixtures in their class.

This series is offered in a wide range of controls and configurations for seamless integration into any building management ecosystem or sensor based platform.

Post + Beam Table Light

METAL SHADE EDITION

LIGHT TYPE

QUANTITY

LW - EB - PB - TB - MS - - DN -

SeriesCollectionModelEditionLHTDriverDimmingLumen OutputColour Temp.WoodFinishAnti-Glare Cell FinishAnti-Glare Cell FinishMetal Shade Finish

Metal Post FinishCable Colour/Cable Length

PARAMETER	SPEC	CODE	DESCRIPTION	CONDITIONALS
01. SERIES		LW-EB	Linear Embedded	
02. COLLECTION		PB	Post + Beam	
03. MODEL		TB	Table Light	
04. EDITION		MS	Metal Shade	
05. BEAM LENGTH (L)			Total length in feet Min. 2' Max. 6' modules Increments of 2' 14.3 W/ft Final length confirmed in shop drawings	Post every 4' or 6' depending on final length. Confirmed in shop drawings
06. LIGHT DISTRIBUTION		DN	Direct	
07. POST HEIGHT (H)			Total height in inches Increments of 1" Min. 12" - Max. 24" Final height confirmed in shop drawings	
08. TABLE THICKNESS (T)			Total thickness in inches	
09. DRIVER		R T P	Remote Remote Under Table Hardwired Remote Under Table 3-Prong Plug	
10. ONSITE DIMMING		010 020 DAL + LUT +	0-10V TRIAC/ELV DALI LUTRON EcoSystem	Not available for P driver Outlet requires dimming compatibility for P driver Not available for P driver Not available for P driver
ONBOARD DIMMING		PS + OS +	Physical Dial Occupancy Sensor (Touchless)	Not available for R driver Not available for R driver
11. LUMEN OUTPUT		LO ST HI	650 lm/ft 6.2 W/ft 115.4 lm/W 1000 lm/ft 9.5 W/ft 110.2 lm/W 1514 lm/ft 14.4 W/ft 104.9 lm/W	
12. COLOUR TEMP		27 30 35 40	2700K 3000K 3500K 4000K	

+ Product upgrade

Post + Beam Table Light

METAL SHADE EDITION

LIGHT TYPE

QUANTITY

LW - EB - PB - TB - MS - - DN -

SeriesCollectionModelEditionLH T Driver Dimming Lumen Output Colour Temp. Wood Finish Anti-Glare Cell Finish Anti-Glare Cell Finish Metal Shade Finish


Metal Post Finish

Cable Colour/
Cable Length


PARAMETER	SPEC	CODE	DESCRIPTION	CONDITIONALS
13. WOOD		WAL	Walnut	
		OAK	White Oak	
		CHR	Cherry	
		MPL	Hard Maple	
		ASH	White Ash	
14. CLEAR FINISH		CFST	Satin	
		CFDO +	Danish Oil	
		CFEC	ECO Zero VOC	
PAINTED FINISH OPTIONAL		PFBK	Satin Black	Parameter for ASH wood types only
		PFWH	Satin White	
		PFXX +	Custom	
15. ANTI-GLARE CELL FINISH		AGNA	Natural Match wood selection	
		AGBS	Black Strip	
		AGWC	White Cell	
16. METAL SHADE FINISH		STAL	Satin Aluminum	
		GLBR	Gold Brushed	
		STGM	Satin Gunmetal	
17. METAL POST FINISH		STST	Stainless Steel	
		PCWH	White Powder Coat	
		PCBK	Black Powder Coat	
		PCXX +	Custom Powder Coat	
		ELBR +	Brass Electroplate	
		ELBZ +	Bronze Electroplate	
18. CABLE COLOUR		B	Black	
		W	White	
19. CABLE LENGTH			In Feet 5' Standard	

CUSTOM NOTES

LIGHTING DIMENSIONS




DRIVER ①



R Remote

Driver is outside of the light fixture in a remote location



T Remote Under Table

Driver is located underneath the table with 3-Prong Plug

SVT-B Flexible Electrical Wire, 3 Conductors, 18 gauge, UL Listed E471215

ONBOARD DIMMING



PS Physical Dial

COLOUR TEMPERATURE ①



27
2700K



30
3000K



35
3500K



40
4000K

WOOD | FSC CERTIFIED ①



WAL
Walnut



OAK
White Oak



CHR
Cherry



MPL
Hard Maple



ASH
White Ash

PAINTED FINISH OPTIONAL ①



PFBK
Satin Black



PFWH
Satin White



PFFX +
Custom

METAL FINISH



STST
Stainless Steel



PCWH
White Powder Coat



PCBK
Black Powder Coat



PCXX +
Custom Powder Coat



ELBR +
Brass Electroplate




ELBZ +
Bronze Electroplate



ELBK +
Black Electroplate

HARDWARE



ANTI-GLARE CELL FINISH ①



AGNA
Natural



AGBS
Black Strip



AGWC
White Cell

METAL SHADE FINISH



STAL
Satin Aluminum



GLBR
Gold Brushed



STGM
Satin Gunmetal

+ Product upgrade