

Star Pendant

PAINTED



SERIES	Star
MODEL	Pendant
EDITION	Painted
LUMEN OUTPUT + CONSUMPTION	28.8 W Max 3022 lm 57.6 W Max 6044 lm <i>Custom lumen output available for Remote fixtures only</i>
POWER INPUT	110-277V AC 50/60 Hz
WEIGHT	< 3 lbs per foot < 4.5 kg per metre
OPTICS	Opal Diffuser
SUSPENSION	Adjustable up to specified length Standard: 5 ft 152 cm
MANUFACTURED IN	Toronto, ON, Canada
WARRANTY	10 year life cycle support 5 year warranty on parts Reclamation program available
CERTIFICATIONS	     

aaline's Star Pendant takes shape through repetition. Planar baffles encircle suspended lighting to achieve unique three-dimensional forms. This system unites engineered wood backed with 100% natural acoustic felt or a painted finish for curated colour combinations and elegant material synergy.

OPEN ONLINE PRODUCT CONFIGURATOR



PROJECT

LIGHT TYPE


QUANTITY

Product design at aaline is continuously refined to uphold the highest quality standards. We reserve the right to change specifications, contact us for the latest information. Final specifications and material selections will be confirmed at the shop drawing stage.


Star Pendant

aaline
architectural lighting + acoustics


05/06. PROFILE + SIZE




S
Linear
1'-10 1/4" Ø x
1'-10 1/2" H




S
Round
1'-10 1/4" Ø x
1'-10 1/2" H




S
Round Short
1'-10 1/4" Ø x
7" H




M
Linear
2'-10 1/4" Ø x
2'-10 1/2" H




M
Round
2'-10 1/4" Ø x
2'-10 1/2" H




M
Round Short
2'-10 1/4" Ø x
11-3/8" H




L
Linear
2'-10 1/4" Ø x
2'-10 1/2" H




L
Round
2'-10 1/4" Ø x
2'-10 1/2" H




L
Round Short
2'-10 1/4" Ø x
11-3/8" H



07. DRIVER



R
Remote
Driver is in a remote location



C
Powered Canopy
Low voltage cable down to fixture
from remote driver canopy mounted to
junction box

10. COLOUR TEMP



27
2700K
Warm White
90+ CRI



30
3000K
Soft White
90+ CRI



35
3500K
Natural White
90+ CRI



40
4000K
Cool White
90+ CRI

Star Pendant


11/12. WOOD SELECTION/WOOD FINISH: CLEAR




Clear finish on EGW will have live edge visible



EGW-CFST
Clear Finish Satin
10 GU @ 60°




EGW-CFDO +
Danish Oil
<5 GU @ 60°



EGW-CFEC
ECO Coat | Zero VOC
<7 GU @ 60°

12. WOOD FINISH: PAINTED



EGW-PFBK
Satin Black
20-35 GU @ 60°




EGW-PFWH
Satin White
20-35 GU @ 60°




EGW-PFXX +
Custom Paint
20-35 GU @ 60°

13. CANOPY DIMENSIONS



Remote Canopy
Driver is in a remote location



Powered Canopy
Driver is in the same room as the fixture

14. CABLE COLOUR



W •
White
Integrated Systems
High-voltage



B
Black
Integrated Systems
High-voltage

16. MOUNTING



PO
Power Over Cable
Low voltage power
over cable hardware



JB
Junction Box Support
Hanging cable at the
centre of the junction box

AALINE RECLAMATION PROGRAM



[Click here for more on Product Life Cycle](#)



Right to Repair

aaline is committed to providing services and support at all stages of the design process, including reclamation and disposal. Please contact us and we will arrange to get the system to our factory so we can refurbish it for you or re-use parts and components that can be reclaimed. Our lighting and acoustic fixtures are made with 100% biodegradable or recyclable materials. The electrical components are RoHS certified and contain no hazardous elements and should be recycled at a specialized recycling facility.

Star Pendant

PRODUCT SPECIFICATION

• PRODUCT STANDARD | + PRODUCT UPGRADE

ST - PN - PT -

01 02 03 04 04 05 06 07 08 09 10 11 12 13 14 15 16

PARAMETER	CODE	DESCRIPTION	CONDITIONALS	NOTES
01. SERIES	ST	Star		
02. MODEL	PN	Pendant		
03. EDITION	PT	Painted		
04. LIGHT TYPE	NON LED	None Integrated LED		Acoustic Only
05. PROFILE	LN RD RS	Linear Round Round Short		
06. SIZE	S M L	Small 2' Ø Medium 3' Ø Large 4' Ø		See product reference for dimensions; Custom upon request. Final dimensions confirmed in shop drawings.
07. DRIVER	R C	Remote Powered Canopy	Parameter for LED light type only	
08. DIMMING	010 • 020	0-10V TRIAC/ELV	Parameter for LED light type only	Reduced warranty, contact us for more info.
09. POWER	28.8W 57.6W XXXXLM	Max 3022 lm Source LED lumens Max 6044 lm Source LED lumens Custom lumen output	Parameter for LED light type only Available for LN and RD profiles only Available for R drivers only	
10. COLOUR TEMP	27K 30K 35K 40K	2700K Warm White 90+ CRI 3000K Soft White 90+ CRI 3500K Natural White 90+ CRI 4000K Cool White 90+ CRI	Parameter for LED light type only	
11. WOOD	EGW	Engineered Wood		Clear finish on EGW will have live edge visible
12. WOOD FINISH: CLEAR	CFST • CFDO + CFEC	Clear Finish Satin Danish Oil ECO Coat Zero VOC		Applied to discs + fins
WOOD FINISH: PAINTED	PFBK PFWH PFXX +	Painted Finish Satin Black Painted Finish Satin White Painted Finish Custom		
13. CANOPY COLOUR	WH • BK XX +	White Black Custom		
14. CABLE COLOUR	W • B	White Black		
15. CABLE LENGTH		In Feet 5' standard • 6' and above +		On-site adjustable
16. MOUNTING	PO JB	Power Over Cable Junction Box	For R drivers only For C drivers only	

CUSTOM NOTES